4N25
4N26
4N27
4N28*

NPN PHOTOTRANSISTOR AND PN INFRARED EMITTING DIODE

. . . Gallium Arsenide LED optically coupled to a Silicon Photo Transistor designed for applications requiring electrical isolation, high-current transfer ratios, small package size and low cost; such as interfacing and coupling systems, phase and feedback controls, solid-state relays and general-purpose switching circuits.

- High Isolation Voltage –
  V_{ISO} = 2500 V (Min) – 4N25
  1500 V (Min) – 4N26, 4N27
  500 V (Min) – 4N28
- High Collector Output Current @ I_F = 10 mA –
  I_C = 5.0 mA (Typ) – 4N25, 4N26
  3.0 mA (Typ) – 4N27, 4N28
- Economical, Compact, Dual-In-Line Package
- Excellent Frequency Response – 300 kHz (Typ)
- Fast Switching Times @ I_C = 10 mA
  t_{on} = 0.87 μs (Typ) – 4N25, 4N26
  2.1 μs (Typ) – 4N27, 4N28
  t_{off} = 11 μs (Typ) – 4N25, 4N26
  5.0 μs (Typ) – 4N27, 4N28

INFRARED LIGHT EMITTING DIODE PHOTOTRANSISTOR COUPLED PAIR

***MAXIMUM RATINGS** (T_A = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
INFRARED EMITTING DIODE MAXIMUM RATINGS			
Reverse Voltage	V_R	3.0	Volts
Forward Current – Continuous	I_F	80	mA
Forward Current – Peak (Pulse Width = 300 μs, 2.0% Duty Cycle)	I_F	3.0	Amp
Total Device Dissipation @ T_A = 25°C Negligible Power in Transistor Derate above 25°C	P_D	150 2.0	mW mW/°C
PHOTOTRANSISTOR MAXIMUM RATINGS			
Collector-Emitter Voltage	V_{CEO}	30	Volts
Emitter-Collector Voltage	V_{ECO}	7.0	Volts
Collector-Base Voltage	V_{CBO}	70	Volts
Total Device Dissipation @ T_A = 25°C Negligible Power in Diode Derate above 25°C	P_D	150 2.0	mW mW/°C
TOTAL DEVICE RATINGS			
Total Device Dissipation @ T_A = 25°C Equal Power Dissipation in Each Element Derate above 25°C	P_D	250 3.3	mW mW/°C
Junction Temperature Range	T_J	-55 to +100	°C
Storage Temperature Range	T_{stg}	-55 to +150	°C
Soldering Temperature (10 s)		260	°C

*Indicates JEDEC Registered Data.



DIM	MILLIMETERS MIN	MILLIMETERS MAX	INCHES MIN	INCHES MAX
A	6.38	6.89	0.330	0.350
B	1.40	1.65	0.055	0.065
C	2.92	3.18	0.115	0.125
D	0.41	0.51	0.016	0.020
E	0.64	0.89	0.025	0.035
F	1.14	1.40	0.045	0.055
G	2.54 BSC		0.100 BSC	
H	1.57	1.83	0.062	0.072
J	0.23	0.28	0.009	0.011
K	2.54	3.30	0.100	0.130
L	7.37	7.87	0.290	0.310
M	–	5°	–	5°
N	–	1.27	–	0.050
R	1.52	1.78	0.060	0.070

CASE 673-03

FIGURE 1 – MAXIMUM POWER DISSIPATION



Figure 1 is based upon using limit values in the equation:

$T_{J1} - T_A = R_{\theta JA} (P_{D1} + K_\theta P_{D2})$

where:

T_{J1} Junction Temperature (100°C)

T_A Ambient Temperature

$R_{\theta JA}$ Junction to Ambient Thermal Resistance (500°C/W)

P_{D1} Power Dissipation in One Chip

P_{D2} Power Dissipation in Other Chip

K_θ Thermal Coupling Coefficient (20%)

Example:

With P_{D1} = 90 mW in the LED @ T_A = 50°C, the transistor P_D (P_{D2}) must be less than 50 mW.

LED CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
*Reverse Leakage Current (V_R = 3.0 V, R_L = 1.0 M ohms)	I_R	–	0.05	100	μA
*Forward Voltage (I_F = 50 mA)	V_F	–	1.2	1.5	Volts
Capacitance (V_R = 0 V, f = 1.0 MHz)	C	–	150	–	pF

PHOTOTRANSISTOR CHARACTERISTICS (T_A = 25°C and I_F = 0 unless otherwise noted)

Characteristic		Symbol	Min	Typ	Max	Unit
*Collector-Emitter Dark Current (V_{CE} = 10 V, Base Open)	4N25, 4N26, 4N27 4N28	I_{CEO}	– –	3.5 –	50 100	nA
*Collector-Base Dark Current (V_{CB} = 10 V, Emitter Open)		I_{CBO}	–	–	20	nA
*Collector-Base Breakdown Voltage (I_C = 100 μA, I_E = 0)		BV_{CBO}	70	–	–	Volts
*Collector-Emitter Breakdown Voltage (I_C = 1.0 mA, I_B = 0)		BV_{CEO}	30	–	–	Volts
*Emitter-Collector Breakdown Voltage (I_E = 100 μA, I_B = 0)		BV_{ECO}	7.0	–	–	Volts
DC Current Gain (V_{CE} = 5.0 V, I_C = 500 μA)		h_{FE}	–	250	–	–

COUPLED CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Typ	Max	Unit
*Collector Output Current (1) (V_{CE} = 10 V, I_F = 10 mA, I_B = 0)	4N25,4N26 4N27,4N28	I_C	2.0 1.0	5.0 3.0	– –	mA
*Isolation Voltage (2)	4N25 4N26,4N27 4N28	V_{ISO}	2500 1500 500	– – –	– – –	Volts
Isolation Resistance (2) (V = 500 V)				10^{11}	–	Ohms
*Collector-Emitter Saturation (I_C = 2.0 mA, I_F = 50 mA)		$V_{CE(sat)}$		0.2	0.5	Volts
Isolation Capacitance (2) (V = 0, f = 1.0 MHz)				1.3	–	pF
Bandwidth (3) (I_C = 2.0 mA, R_L = 100 ohms, Figure 11)				300	–	kHz

SWITCHING CHARACTERISTICS

Delay Time	(I_C = 10 mA, V_{CC} = 10 V)	4N25,4N26 4N27,4N28	t_d	– –	0.07 0.10	– –	μs
Rise Time	Figures 6 and 8	4N25,4N26 4N27,4N28	t_r	– –	0.8 2.0	– –	μs
Storage Time	(I_C = 10 mA, V_{CC} = 10 V)	4N25,4N26 4N27,4N28	t_s	– –	4.0 2.0	– –	μs
Fall Time	Figures 7 and 8	4N25,4N26 4N27,4N28	t_f	– –	7.0 3.0	– –	μs

*Indicates JEDEC Registered Data. (1) Pulse Test: Pulse Width = 300 μs, Duty Cycle = 2.0%.
(2) For this test LED pins 1 and 2 are common and Photo Transistor pins 4, 5 and 6 are common.
(3) I_F adjusted to yield I_C = 2.0 mA and i_c = 2.0 mA p-p at 10 kHz.

DC CURRENT TRANSFER CHARACTERISTICS

FIGURE 2 – 4N25, 4N26



FIGURE 3 – 4N27, 4N28



TYPICAL ELECTRICAL CHARACTERISTICS

FIGURE 4 – DIODE FORWARD CHARACTERISTICS



FIGURE 5 – COLLECTOR SATURATION VOLTAGE



FIGURE 6 – TURN-ON TIME



FIGURE 7 – TURN-OFF TIME



FIGURE 8 – SATURATED SWITCHING TIME TEST CIRCUIT



FIGURE 9 – DARK CURRENT versus AMBIENT TEMPERATURE



FIGURE 10 – FREQUENCY RESPONSE



FIGURE 11 – FREQUENCY RESPONSE TEST CIRCUIT



TYPICAL APPLICATIONS

FIGURE 12 – ISOLATED MTTL TO MOS (P-CHANNEL) LEVEL TRANSLATOR



FIGURE 13 – COMPUTER/PERIPHERAL INTERCONNECT



FIGURE 14 – POWER AMPLIFIER



FIGURE 15 – INTERFACE BETWEEN LOGIC AND LOAD



Typical Electrical Characteristics

4N35
4N36
4N37

Electrical Characteristics—Input Diode $T_A = 25°C$

Symbol	Characteristic	Min	Typ	Max	Units	Test Conditions
V_F*	Forward Voltage	0.8		1.5	V	I_F = 10 mA
I_R*	Reverse Leakage Current		0.01	10	μA	V_R = 6.0 V
C	Capacitance			100	pF	V_R = 0 V, f = 1 MHz

Electrical Characteristics—Output Transistor $T_A = 25°C$

Symbol	Characteristic	Min	Typ	Max	Units	Test Conditions
V_{CEO}*	Collector-to-Emitter Voltage	30	65		V	I_C = 10 mA
V_{CBO}*	Collector-to-Base Voltage	70	165		V	I_C = 100 μA
V_{ECO}*	Emitter-to-Collector Voltage	7.0	14		V	I_E = 100 μA, I_F = 0
I_{CEO}*	Collector-to-Emitter Leakage Current		5.0	50	nA	V_{CE} = 10 V, I_F = 0
I_{CEO}*	Collector-to-Emitter Leakage Current			500	μA	V_{CE} = 30 V, I_F = 0, T_A = 100°C
h_{FE}	Forward Current Gain	100	250			V_{CE} = 5.0 V, I_C = 100 μA
C_{cb}	Collector-to-Base Capacitance		25		pF	V_{CB} = 10 V

Electrical Characteristics—Coupled $T_A = 25°C$

Symbol	Characteristic	Min	Typ	Max	Units	Test Conditions
I_{IO}*	Input-to-Output Current					PW = 8 ms
	4N35			100	μA	V_{IO} = 3550 V
	4N36			100	μA	V_{IO} = 2500 V
	4N37			100	μA	V_{IO} = 1500 V
$V_{CE(sat)}$*	Collector-to-Emitter Saturation Voltage			0.3	V	I_C = 0.5 mA, I_F = 10 mA
$I_C/I_F(CTR)$*	Collector Current Transfer Ratio (Note)	100			%	V_{CE} = 10 V, I_F = 10 mA
$I_C/I_F(CTR)$*	Collector Current Transfer Ratio (Note)	40			%	V_{CE} = 10 V, I_F = 10 mA, T_A = −55°C to 100°C
R_{IO}	Input-to-Output Resistance	10^{11}			Ω	V_{IO} = 500 V
C_{IO}	Input-to-Output Capacitance		1.0	2.5	pF	V_{IO} = 0, f = 1.0 MHz
t_{on}	Turn-on Time		5.0	10	μs	I_C = 2.0 mA, V_{CC} = 10 V, R_L = 100 Ω
t_{off}	Turn-off Time		5.0	10	μs	I_C = 2.0 mA, V_{CC} = 10 V, R_L = 100 Ω

Notes
Collector current transfer ratio is defined as the ratio of the collector current to the forward bias input current.
*Indicates JEDEC registered values.

LSTTL/T
Optocou
Optoelectronic Pr

General Descripti
The 6N137 optoc
emitting diode an
is collected in the
is amplified by a h
Schottky-clampe
Temperature, cur
the circuit.

This isolator desi
patibility while at
isolation betweer
ates from a 5 V s
to sink at least 1
to 70°C tempera
rent is 5 mA. Wh
isolating mode, t
An LSTTL/TTL-c
gates the output
ns.

The 6N137 is ap
subsystems that
tials, signal level
common-mode n
programmable flo
other machine co

LSTTL/TTL Cor
Ultra High Spee
Low Input Curre
High Common-M
Guaranteed Per
3000 V dc Insul

Absolute Maxim
Up to 70°C)

Maximum Temp
Operating Temp
Storage Temper
Pin Temperature
(1.6 mm below s

Maximum Powe
Output Collector
Dissipation

*JEDEC Registered

Optically-Coupled Isolator

Optoelectronic Products

4N35
4N36
4N37

General Description

The 4N35, 4N36 and 4N37 series of optoisolators has a silicon npn Planar phototransistor in close proximity to a GaAs diode. Optical coupling provides a high degree of ac and dc isolation. A capability for continuous operation of the input diode results in a frequency response extending to dc. Connection to the transistor base is also provided for design flexibility. This isolator series is covered under UL component recognition program, reference file E55299.

Glassolated™
High Current Transfer Ratio—Minimum 100%
1500 V to 3500 V Minimum Isolation Input-to-Output
10^{11} Ω Isolation Resistance
Low Coupling Capacitance—Typically 1.0 pF

Absolute Maximum Ratings

Maximum Temperature and Humidity

Storage Temperature*	−55°C to +150°C
Operating Temperature	−55°C to +100°C
Pin Temperature (Soldering, 10s)*	260°C
Relative Humidity at 85°C*	85%

Input Diode

V_R*	Reverse Voltage	6.0 V
I_F*	Forward Current	60 mA
I_{pk}*	Peak Forward Current at 1 μs pulse width, 300 pps	3.0 A
P_D*	Power Dissipation at T_A = 25°C	100 mW
	Derate Linearly from 25°C	1.33 mW/°C

Output Transistor

V_{CE}*	Collector-to-Emitter Voltage	30 V
V_{CB}*	Collector-to-Base Voltage	70 V
V_{EC}*	Emitter-to-Collector Voltage	7.0 V
I_C*	Collector Current	100 mA
P_D*	Power Dissipation at T_A = 25°C	300 mW
	Derate Linearly from 25°C	4.0 mW/°C

*Indicates JEDEC registered values.

Package Outline



Notes
All dimension in inches bold and millimeters (parentheses)
Tolerance unless specified = ±0.15 (0.381)

Connection Diagram
DIP (Top View)



Pin		
1	Anode (+)	Input Diode
2	Cathode (−)	Input Diode
3	NC	Output npn Phototransistor
4	Emitter	Output npn Phototransistor
5	Collector	Output npn Phototransistor
6	Base	Output npn Phototransistor

BULLETIN NO. DL-S 7312030, NOVEMBER 1973

COMPATABLE WITH STANDARD DTL AND TTL INTEGRATED CIRCUITS

- Gallium Arsenide Diode Infrared Source Optically Coupled to a Silicon N-P-N Phototransistor
- High Direct-Current Transfer Ratio
- Base Lead Provided for Conventional Transistor Biasing
- High-Voltage Electrical Isolation . . . 1.5-kV or 2.5-kV Rating
- Plastic Dual-In-Line Package
- High-Speed Switching: t_r = 2 μs, t_f = 2 μs Typical

mechanical data

The package consists of a gallium arsenide infrared-emitting diode and an n-p-n silicon phototransistor mounted on a 6-lead frame encapsulated within an electrically nonconductive plastic compound. The case will withstand soldering temperature with no deformation and device performance characteristics remain stable when operated in high-humidity conditions. Unit weight is approximately 0.52 grams.



NOTES:
a. Leads are within 0.005 radius of true position (TP) at the gauge plane with maximum material condition and unit installed.
b. All dimensions are in inches unless otherwise noted.
c. Pin 1 identified by index dot.
d. Terminal connections:
   1. Anode } Infrared-emitting diode
   2. Cathode }
   3. No internal connection
   4. Emitter } Phototransistor
   5. Collector }
   6. Base }

absolute maximum ratings at 25°C free-air temperature (unless otherwise noted)

Input-to-Output Voltage: TIL111	±1.5 kV
TIL114, TIL116, TIL117	±2.5 kV
Collector-Base Voltage	70 V
Collector-Emitter Voltage (See Note 1)	30 V
Emitter-Collector Voltage	7 V
Emitter-Base Voltage	7 V
Input-Diode Reverse Voltage	3 V
Input-Diode Continuous Forward Current at (or below) 25°C Free-Air Temperature (See Note 2)	100 mA
Continuous Power Dissipation at (or below) 25°C Free-Air Temperature:	
Infrared-Emitting Diode (See Note 3)	150 mW
Phototransistor (See Note 4)	150 mW
Total, Infrared-Emitting Diode plus Phototransistor (See Note 5)	250 mW
Storage Temperature Range	−55°C to 150°C
Lead Temperature 1/16 Inch from Case for 10 Seconds	260°C

NOTES: 1. This value applies when the base-emitter diode is open-circuited.
2. Derate linearly to 100°C free-air temperature at the rate of 1.33 mA/°C.
3. Derate linearly to 100°C free-air temperature at the rate of 2 mW/°C.
4. Derate linearly to 100°C free-air temperature at the rate of 2 mW/°C.
5. Derate linearly to 100°C free-air temperature at the rate of 3.33 mW/°C.

TYPES TIL111, TIL114, TIL116, TIL117
OPTO-COUPLERS

electrical characteristics at 25°C free-air temperature

PARAMETER			TEST CONDITIONS	TIL111 TIL114			TIL116			TIL117			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage		I_C = 10 μA, I_E = 0, I_F = 0	70			70			70			V
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage		I_C = 1 mA, I_B = 0, I_F = 0	30			30			30			V
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage		I_E = 10 μA, I_C = 0, I_F = 0	7			7			7			V
I_R	Input Diode Static Reverse Current		V_R = 3 V			10			10			10	μA
$I_{C(on)}$	On-State Collector Current	Phototransistor Operation	V_{CE} = 0.4 V, I_F = 16 mA, I_B = 0	2	7								mA
			V_{CE} = 10 V, I_F = 10 mA, I_B = 0				2	5		5	9		
		Photodiode Operation	V_{CB} = 0.4 V, I_F = 16 mA, I_E = 0	10	20		10	20		10	20		μA
$I_{C(off)}$	Off-State Collector Current	Phototransistor Operation	V_{CE} = 10 V, I_F = 0, I_B = 0		1	50		1	50		1	50	nA
		Photodiode Operation	V_{CB} = 10 V, I_F = 0, I_E = 0		0.1	20		0.1	20		0.1	20	
h_{FE}	Transistor Static Forward Current Transfer Ratio		V_{CE} = 5 V, I_C = 10 mA, I_F = 0	100	300					200	550		
			V_{CE} = 5 V, I_C = 100 μA, I_F = 0				100	300					
V_F	Input Diode Static Forward Voltage		I_F = 16 mA		1.2	1.4					1.2	1.4	V
			I_F = 60 mA					1.25	1.5				
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage		I_C = 2 mA, I_F = 16 mA, I_B = 0		0.25	0.4							V
			I_C = 2.2 mA, I_F = 15 mA, I_B = 0					0.25	0.4				
			I_C = 0.5 mA, I_F = 10 mA, I_B = 0								0.25	0.4	
r_{IO}	Input-to-Output Internal Resistance		V_{in-out} = ±1.5 kV for TIL111, ±2.5 kV for all others, See Note 6	10^{11}			10^{11}			10^{11}			Ω
C_{io}	Input-to-Output Capacitance		V_{in-out} = 0, f = 1 MHz, See Note 6		1	1.3		1	1.3		1	1.3	pF

NOTE 6: These parameters are measured between both input-diode leads shorted together and all the phototransistor leads shorted together.

switching characteristics at 25°C free-air temperature

PARAMETER			TEST CONDITIONS	TIL111 TIL114			TIL116			TIL117			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
t_r	Rise Time	Phototransistor Operation	V_{CC} = 10 V, $I_{C(on)}$ = 2 mA, R_L = 100 Ω, See Test Circuit A of Figure 1		2	5		2	7		2	9	μs
t_f	Fall Time				2	5		2	7		2	9	
t_r	Rise Time	Photodiode Operation	V_{CC} = 10 V, $I_{C(on)}$ = 20 μA, R_L = 1 kΩ, See Test Circuit B of Figure 1		1			1			1		μs
t_f	Fall Time				1			1			1		



TEST CIRCU
PHOTOTRANSISTOR

NOTES: a. The input
t_w = 100 μ
b. The outpu



PARAMETER MEASUREMENT INFORMATION



TEST CIRCUIT A
PHOTOTRANSISTOR OPERATION

VOLTAGE WAVEFORMS

TEST CIRCUIT B
PHOTODIODE OPERATION

NOTES: a. The input waveform is supplied by a generator with the following characteristics: $Z_{out} = 50\ \Omega$, $t_r \leq 15$ ns, duty cycle ≈ 1%, $t_w = 100\ \mu s$.
b. The output waveform is monitored on an oscilloscope with the following characteristics: $t_r \leq 12$ ns, $R_{in} \geq 1\ M\Omega$, $C_{in} \leq 20$ pF.

FIGURE 1–SWITCHING TIMES

TYPICAL CHARACTERISTICS

TIL111, TIL114
COLLECTOR CURRENT
vs
INPUT-DIODE FORWARD CURRENT



FIGURE 2

TIL116, TIL117
COLLECTOR CURRENT
vs
INPUT-DIODE FORWARD CURRENT



FIGURE 3

TYPICAL CHARACTERISTICS

TIL111, TIL114

COLLECTOR CURRENT
vs
COLLECTOR-EMITTER VOLTAGE



FIGURE 4

TIL116

COLLECTOR CURRENT
vs
COLLECTOR-EMITTER VOLTAGE



FIGURE 5

TIL117

COLLECTOR CURRENT
vs
COLLECTOR-EMITTER VOLTAGE



FIGURE 6

RELATIVE ON-STATE COLLECTOR CURRENT
vs
FREE-AIR TEMPERATURE



FIGURE 7

NOTES: 7. Pulse operation of input diode is required for operation beyond limits shown by dotted lines.
8. These parameters were measured using pulse techniques. t_w = 1 ms, duty cycle < 2%.

TEXAS INSTRUMENTS
INCORPORATED
POST OFFICE BOX 5012 • DALLAS, TEXAS 75222

TYPICAL CHARACTERISTICS

OFF-STATE COLLECTOR CURRENT
vs
FREE-AIR TEMPERATURE



FIGURE 8

NORMALIZED TRANSISTOR STATIC FORWARD
CURRENT TRANSFER RATIO
vs
ON-STATE COLLECTOR CURRENT



FIGURE 9

INPUT DIODE FORWARD
CONDUCTION CHARACTERISTICS



FIGURE 10

COLLECTOR CURRENT
vs
MODULATION FREQUENCY



FIGURE 11

NOTE 8: These parameters were measured using pulse techniques. t_w = 1 ms, duty cycle ≤ 2%.

TYPES TIL112, TIL115, TIL118
OPTOCOUPLERS

D1607, NOVEMBER 1973—REVISED FEBRUARY 1983

- Gallium Arsenide Diode Infrared Source Optically Coupled to a Silicon N-P-N Phototransistor
- High Direct-Current Transfer Ratio
- Base Lead Provided for Conventional Transistor Biasing (TIL112, TIL115)
- High-Voltage Electrical Isolation . . . 1.5-kV or 2.5-kV Rating
- Plastic Dual-In-Line Package
- High-Speed Switching: $t_r = 2\ \mu s$, $t_f = 2\ \mu s$ Typical

mechanical data

The package consists of a gallium arsenide infrared-emitting diode and an n-p-n silicon phototransistor mounted on a 6-lead frame encapsulated within an electrically nonconductive plastic compound. The case will withstand soldering temperature with no deformation and device performance characteristics remain stable when operated in high-humidity conditions. Unit weight is approximately 0.52 grams.



absolute maximum ratings at 25°C free-air temperature (unless otherwise noted)

	TIL112	TIL115	TIL118
Input-to-Output Voltage	±1.5 kV	±2.5 kV	±1.5 kV
Collector-Base Voltage	30 V	30 V	
Collector-Emitter Voltage (See Note 1)	20 V	20 V	20 V
Emitter-Collector Voltage	4 V	4 V	4 V
Emitter-Base Voltage	4 V	4 V	
Input-Diode Reverse Voltage	3 V	3 V	3 V
Input-Diode Continuous Forward Current at (or below) 25°C Free-Air Temperature (See Note 2)	100 mA		
Continuous Power Dissipation at (or below) 25°C Free-Air Temperature:			
Infrared-Emitting Diode (See Note 3)	150 mW		
Phototransistor (See Note 4)	150 mW		
Total (Infrared-Emitting Diode plus Phototransistor, See Note 5)	250 mW		
Storage Temperature Range	−55°C to 150°C		
Lead Temperature 1,6 mm (1/16 Inch) from Case for 10 Seconds	260°C		

NOTES: 1. This value applies when the base-emitter diode is open-circuited.
2. Derate linearly to 100°C free-air temperature at the rate of 1.33 mA/°C.
3. Derate linearly to 100°C free-air temperature at the rate of 2 mW/°C.
4. Derate linearly to 100°C free-air temperature at the rate of 2 mW/°C.
5. Derate linearly to 100°C free-air temperature at the rate of 3.33 mW/°C.

electrical characteristics at 25°C free-air temperature

PARAMETER			TEST CONDITIONS†	TIL112			TIL115			TIL118			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage		I_C = 10 μA, I_E = 0, I_F = 0	30			30						V
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage		I_C = 1 mA, I_B = 0, I_F = 0	20			20			20			V
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage		I_E = 10 μA, I_C = 0, I_F = 0	4			4						V
$V_{(BR)ECO}$	Emitter-Collector Breakdown Voltage		I_E = 10 μA, I_F = 0							4			V
$I_{C(on)}$	On-State Collector Current	Phototransistor Operation	V_{CE} = 5 V, I_F = 10 mA, I_B = 0	0.2	2		0.2	2		1	2		mA
		Photodiode Operation	V_{CB} = 5 V, I_F = 10 mA, I_E = 0	2	10		2	10					μA
$I_{C(off)}$	Off-State Collector Current	Phototransistor Operation	V_{CE} = 5 V, I_F = 0, I_B = 0		1	100		1	100		1	100	nA
		Photodiode Operation	V_{CB} = 5 V, I_F = 0, I_E = 0		0.1	50		0.1	50				
h_{FE}	Transistor Static Forward Current Transfer Ratio		V_{CE} = 5 V, I_C = 10 mA, I_F = 0	50	200		50	200					
V_F	Input Diode Static Forward Voltage		I_F = 10 mA		1.2	1.5		1.2	1.5		1.2	1.5	V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage		I_C = 2 mA, I_F = 50 mA, I_B = 0			0.5			0.5			0.5	V
r_{IO}	Input-to-Output Internal Resistance		V_{in-out} = ±1.5 kV, See Note 6	10^{11}						10^{11}			Ω
			V_{in-out} = ±2.5 kV, See Note 6				10^{11}						
C_{io}	Input-to-Output Capacitance		V_{in-out} = 0, f = 1 MHz, See Note 6		1	2		1	2		1	2	pF

NOTE 6: These parameters are measured between both input-diode leads shorted together and all the phototransistor leads shorted together.
†References to the base are not applicable for the TIL118.

switching characteristics at 25°C free-air temperature

PARAMETER			TEST CONDITIONS	TIL112			TIL115			TIL118			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
t_r	Rise Time	Phototransistor Operation	V_{CC} = 10 V, $I_{C(on)}$ = 2 mA, R_L = 100 Ω, See Test Circuit A of Figure 1		2	15		2	15		2	15	μs
t_f	Fall Time				2	15		2	15		2	15	
t_r	Rise Time	Photodiode Operation	V_{CC} = 10 V, $I_{C(on)}$ = 20 μA, R_L = 1 kΩ, See Test Circuit B of Figure 1		1			1					μs
t_f	Fall Time				1			1					

PARAMETER MEASUREMENT INFORMATION



TEST CIRCUIT A
PHOTOTRANSISTOR OPERATION

VOLTAGE WAVEFORMS

TEST CIRCUIT B
PHOTODIODE OPERATION

NOTES: a. The input waveform is supplied by a generator with the following characteristics: Z_{out} = 50 Ω, t_r ≤ 15 ns, duty cycle ≈ 1%, t_w = 100 μs.
b. The output waveform is monitored on an oscilloscope with the following characteristics: t_r ≤ 12 ns, R_{in} ≥ 1 MΩ, C_{in} ≤ 20 pF.

FIGURE 1–SWITCHING TIMES

TYPICAL CHARACTERISTICS



FIGURE 2



FIGURE 3



FIGURE 4

NOTES: 7. Pulse operation of input diode is required for operation beyond limits shown by dotted lines.
8. These parameters were measured using pulse techniques t_w = 1 ms, duty cycle ≤ 2%.

TYPICAL CHARACTERISTICS

OFF-STATE COLLECTOR CURRENT
vs
FREE-AIR TEMPERATURE



FIGURE 5

NORMALIZED TRANSISTOR STATIC FORWARD
CURRENT TRANSFER RATIO
vs
ON-STATE COLLECTOR CURRENT



FIGURE 6

INPUT DIODE FORWARD
CONDUCTION CHARACTERISTICS



FIGURE 7

COLLECTOR CURRENT
vs
MODULATION FREQUENCY



FIGURE 8

NOTE 8: These parameters were measured using pulse techniques. t_w = 1 ms, duty cycle ≤ 2%.

D1499, AUGUST 1981–REVISED FEBRUARY 1983

- Gallium Arsenide Diode Infrared Source Optically Coupled to a Silicon N-P-N Darlington-Connected Phototransistor
- High Direct-Current Transfer Ratio . . . 300% Minimum at 10 mA
- High-Voltage Electrical Isolation . . . 1500-Volt Rating
- Plastic Dual-In-Line Package
- Base Lead Provided on TIL113 for Conventional Transistor Biasing
- No Base Lead Connection on TIL119A for High-EMI Environments
- Typical Applications Include Remote Terminal Isolation, SCR and Triac Triggers, Mechanical Relays, and Pulse Transformers

mechanical data

The package consists of a gallium arsenide infrared-emitting diode and an n-p-n silicon darlington-connected phototransistor mounted on a 6-lead frame encapsulated within an electrically nonconductive plastic compound. The case will withstand soldering temperature with no deformation and device performance characteristics remain stable when operated in high-humidity conditions. Unit weight is approximately 0.52 grams.



absolute maximum ratings at 25°C free-air temperature (unless otherwise noted)

Input-to-Output Voltage	±1.5 kV
Collector-Base Voltage (TIL113)	30 V
Collector-Emitter Voltage (See Note 1)	30 V
Emitter-Collector Voltage	7 V
Emitter-Base Voltage (TIL113)	7 V
Input-Diode Reverse Voltage	3 V
Input-Diode Continuous Forward Current at (or below) 25°C Free-Air Temperature (See Note 2)	100 mA
Continuous Power Dissipation at (or below) 25°C Free-Air Temperature:	
Infrared-Emitting Diode (See Note 3)	150 mW
Phototransistor (See Note 4)	150 mW
Total (Infrared-Emitting Diode plus Phototransistor, See Note 5)	250 mW
Storage Temperature Range	−55°C to 150°C
Lead Temperature 1,6 mm (1/16 Inch) from Case for 10 Seconds	260°C

NOTES: 1. This value applies when the base-emitter diode is open-circuited.
2. Derate linearly to 100°C free-air temperature at the rate of 1.33 mA/°C.
3. Derate linearly to 100°C free-air temperature at the rate of 2 mW/°C.
4. Derate linearly to 100°C free-air temperature at the rate of 2 mW/°C.
5. Derate linearly to 100°C free-air temperature at the rate of 3.33 mW/°C.